



Box (20 m3)

14 mm Fibreglass Reinforced Plywood panel

EUROPAL execution – bonding assembly without visible mechanical fixings on the outside

Option : lightweight panel with a polyethylene PET foam core (80 Kg in weight savings)

Rear Frame

Bolted rear frame – no welding

Mill finish vertical aluminium uprights

Top and bottom cross-members are galvanised steel

270° opening barn doors in 30 mm insulated panel

1 stainless steel recessed lock on right door leaf + budget lock on left one

Rear marker lights are inset in to the rear frame as standard

Brake light available as an optional extra

► OPTIONAL EXTRAS



- Polyester nose cone
- Upward opening access 440 x 420 mm on front bulkhead
- Single swing door 1030 x max. high → 1 200 mm back from bulkhead



- Aluminium or galvanised steel skirting plate
- Lashing rails, lashing tubes, interior protection for removing cargo

- Recessed lock on left door leaf
- Roller shutter door
- Top flap in combination with tail-lift
- Mudwings – side-guards
- Footsteps (4 rungs)



Sub-frame

Mill finish aluminium sub-frame in kit format

- Aluminium longitudines
- Aluminium cross-members

Optional Extras :

- Mudwings – side-guards
- Footsteps (4 rungs)
- Floor sheets 15 mm thick

Roof

Mill finish aluminium profiles

One piece semi-translucent roof riveted to the roof frame

<u>Body dimensions (mm)</u>	<u>External</u>	<u>Internal</u>
<u>Length</u>	4 300	4 250
<u>Width</u>	2 150 or 2 200	2 100 or 2 150
<u>Door aperture Width</u>	1 990	2 040
<u>Internal Height</u>	1 950-2 200-2 300	
<u>Door aperture Height</u>	1 900-2 150-2 250	

