



LIGHTWEIGHT PANEL Kit

Range : 6,5 tonne GVW rating max.

Family : Lightweight

Execution : **EUROPAL**

BODY DIMENSIONS (mm)

External length : 1 500 to 5 400 mm

External width : 2 350 mm max.

Internal height :

2 350 mm max. with top flap

2 400 mm max. with 2 barn doors

REAR FRAME

- Bolted rear frame, no welding
- Mill finish or anodised vertical aluminium uprights
- Top and bottom cross-members are either galvanised steel or stainless steel
- 270° opening barn doors in 30 mm insulated panel
- 1 stainless steel recessed lock on right door leaf

OPTIONAL EXTRAS

- Steel rear frame
- Top flap in combination with tail-lift
- Roller shutter door
- No rear frame – solid panel front and rear

SIDE PANELS

- 17 mm lightweight panels
- Smooth polyester surfaces (colour based on white RAL 9010)
- Panels with a high density PET foam core (weight **5,2 kg/m²**)

OPTIONAL EXTRAS

- Lashing rails, lashing tubes, interior protection for removing cargo
- Aluminium or galvanised steel skirting plate
- Single swing door, double swing door or sliding door
- Roll-up door



FRONT BULKHEAD

- 17 mm Fibreglass Reinforced Plywood panel or 17 mm lightweight panel

OPTIONAL EXTRAS

- Lashing rails, lashing tubes, interior protection for removing cargo
- Aluminium or galvanised steel skirting plate
- Upward opening access – sliding access
- Polyester nose cone

ROOF

- Mill finish or anodised aluminium profiles
- One piece semi-translucent or white opaque roof riveted to the roof frame

OPTIONAL EXTRAS

- Clear light or translucent strip
- Ceiling light (12 LED lamps)

SUB-FRAME (optional extra)

- Mill finish aluminium sub-frame in kit format
- Aluminium longitudes
- Aluminium cross-members

OPTIONAL EXTRAS

- Mudwings - side-guards
- Footsteps (4 rungs)

