

SMOOTH ALUMINIUM Kit

Range : 6,5 tonne GVW rating max.

Family : Aluminium

Execution : **EUROPAL**



BODY DIMENSIONS (mm)

External length : 1 500 to 6 000 mm

External width : 2 350 mm max.

Internal height :

2 350 mm max. with top flap

2 400 mm max. with 2 barn doors

REAR FRAME

- Bolted rear frame – no welding
- Mill finish or anodised vertical aluminium uprights
- Top and bottom cross-members are either galvanised steel or stainless steel
- 270° opening barn doors in 30 mm insulated panel
- 1 stainless steel recessed lock on right door leaf

OPTIONAL EXTRAS

- Steel rear frame
- Top flap in combination with tail-lift
- Roller shutter door
- No rear frame – solid panel front and rear

SIDE WALLS

- All aluminium
- Aluminium panels of 583 mm or 375 mm wide assembled with clamped aluminium uprights
- Smooth surfaces on all external panels (colour based on white RAL 9016)
- Front and rear upright profiles designed for a quick fixing to the front bulkhead and rear frame

OPTIONAL EXTRAS

- Lashing rails, lashing tubes, interior protection for removing cargo
- Single swing door, double swing door or sliding door



FRONT BULKHEAD

- All aluminium
- Aluminium panels of 583 mm or 375 mm wide assembled with clamped aluminium uprights
- Smooth surfaces on all external panels (colour based on white RAL 9016)
- Round aluminium profiles for a quick fixing to side walls

OPTIONAL EXTRAS

- Lashing rails, lashing tubes, interior protection for removing cargo

ROOF

- Mill finish or anodised aluminium profiles
- One piece semi-translucent or white opaque roof riveted to the roof frame

OPTIONAL EXTRAS

- Clear light or translucent strip
- Ceiling light (12 LED lamps)

SUB-FRAME (Optional extra)

- Mill finish aluminium sub-frame in kit format
- Aluminium longitudes
- Aluminium cross-members

OPTIONAL EXTRAS

- Mudwings - side-guards
- Footsteps (4 rungs)

