

POLYESTER SKIN Kit

Range : 6,5 tonne GVW rating max.

Family : Polyester

Execution : **EUROPAL**



BODY DIMENSIONS (mm)

External length : 4 500 mm max.

External width : 2 350 mm

Internal height : 2 300 mm max.

REAR FRAME

- Bolted rear frame – no welding
- Mill finish or anodised vertical aluminium uprights
- Top and bottom cross-members are either galvanised steel or stainless steel
- 270° opening barn doors in 30 mm insulated panel
- 1 stainless steel recessed lock on right door leaf

OPTIONAL EXTRAS

- Steel rear frame
- Top flap in combination with tail-lift
- Roller shutter door
- No rear frame – solid panel front and rear

SIDE WALLS

- 3 mm polyester skin – 2 sides
- Vertical aluminium uprights (40x25) bonded at the interval of 460 mm and fitted to the top and bottom profiles
- Smooth surfaces on all external panels (colour based on white RAL 9016)

OPTIONAL EXTRAS

- Lashing rails, lashing tubes, interior protection for removing cargo
- Single swing door – Aperture width 1030 mm



FRONT BULKHEAD

- Polyester skin (colour based on white RAL 9016) or 14 mm Fibreglass Reinforced Plywood panel

OPTIONAL EXTRAS

- Lashing rails, lashing tubes, interior protection for removing cargo
- Upward opening access – sliding access (14 mm FRP panels only)
- Polyester nose cone

ROOF

- Mill finish or anodised aluminium profiles
- One piece semi-translucent or white opaque roof riveted to the roof frame

OPTIONAL EXTRAS

- Insulated roof (steel rear frame only)
- Clear light or translucent strip
- Ceiling light (12 LED lamps)

SUB-FRAME (Optional extra)

- Mill finish aluminium sub-frame in kit format
- Aluminium longitudes
- Aluminium cross-members

OPTIONAL EXTRAS

- Mudwings - side-guards
- Footsteps (4 rungs)

