



Kit OPENBOX LIGHT

Range : GVW 6,5 ton ratings max.

Family : Curtain side body

Execution : **EUROPAL**



REAR FRAME

- Bolted rear frame – no welding
- Mill finish or anodized aluminium uprights
- Top and bottom cross-members in galvanized steel or stainless steel
- 270° opening barn doors in 30 mm insulated panel
- 1 stainless steel recessed lock on right door leaf

OPTIONAL EXTRAS

- Top flap in combination with tail-lift
- Roller shutter door
- No doors – rear panel same as front

SIDE WALLS

- Vertical aluminium planks 107 mm wide
- Galvanized side rails with integrated pallet retainer
- Galvanized side rail rails
- Zinc plated steel carriers
- Zinc plated side locks (key barrel) and top rubber pelmet
- 650 gr/sqm curtain fanfold

OPTIONAL EXTRAS

- Side wall in 14 mm FRP panel or in smooth aluminium
- Galvanized skirting board
- Lashing rails

DIMENSIONS (mm)

External length : 3 755 to 5 255
(pitch of 100 mm)

External width : 2 350 mm max.

Internal height : 1 800 to
2 350 mm max. with top flap
2 400 mm max. with 2 barn doors

FRONT BULKHEAD

- 14 mm FRP panel or in aluminium modular assembly with panels of 583 mm wide

OPTIONAL EXTRAS

- Galvanized skirting board
- Lashing rails
- Trap door – sliding trap door (14 mm FRP panel only)
- Polyester nose cone

ROOF

- Mill finish or anodized aluminium profiles
- One piece aluminium or translucent roof riveted to the roof frame

OPTIONAL EXTRAS

- Clear light or translucent strip
- 30 mm insulated panel
- Ceiling light (4 LED lamps)

SUB-FRAME (Optional extra)

- Mill finish aluminium sub-frame in kit format
- Main beams in aluminium
- Cross-members in aluminium or galvanized steel

OPTIONAL EXTRAS

- Mudwings - side-guards
- Footsteps (4 rungs)

