





REAR FRAME

- Bolted rear frame, no welding
- Mill finish or anodized aluminium uprights
- Top and bottom cross-members in galvanized steel or stainless steel
- 270° opening barn doors in 30 mm insulated panel
 1 stainless steel recessed lock on right door leaf

OPTIONAL EXTRAS

- Top flap in combination with tail-lift
- No door rear panel same as front

SIDE PANELS

- Stainless steel handle integrated in front and rear corner posts
- Aluminium uprights (3 or 5 per side according to the body length)
- Galvanized side rave rails
- 630 gr/sqm curtain fanfold
- Automaticity of the opening realized with the aid of elastic cords and pulleys
- Pre-selection of the segments to open with aluminium laths

OPTIONAL EXTRAS

- Side wall closed with a panel
- Lashing rails, lashing tubes, interior protections for removal box

Kit SPEEDBOX

Range: GVW 6,5 ton ratings max.

Family: FRP panel/aluminium – Curtain side body

Execution: EUROPAL

DIMENSIONS (mm)

External length: 3 500 to 5 400 mm External width: 2 350 mm max.

Internal height:

2 350 mm max. with top flap

2 400 mm max. with 2 barn doors

FRONT BULKHEAD

▶ 14 mm FRP panel or in aluminium modular assembly with panels of 583 mm wide

OPTIONAL EXTRAS

- Lashing rails, lashing tubes, interior protections for removal box
- Trap door sliding trap door (14 mm FRP panel only)
- · Polyester nose cone

ROOF

- Mill finish or anodized aluminium profiles
- 1 piece aluminium or translucent roof riveted to the roof frame

OPTIONAL EXTRAS

- Clear light or translucent strip
- 30 mm insulated panel
- Ceiling light (4 LED lamps)

SUB-FRAME (optional extra)

- Mill finish aluminium sub-frame in kit format
- > Main beams in aluminium
- Cross-members in aluminium or galvanized steel

OPTIONAL EXTRAS

- Mudwings side-guards
- Footsteps (4 rungs)





